

SEPTEMBER 2018

ORIUM

The reliable tyre offer
for economical transports



The right direction

orium-tyres.com

ORIUM, the reliable choice for an economical



ORIUM ROAD GO

MEDIUM TRUCK & LOW-BED TRAILER
REGIONAL & LONG HAUL USE



STEER / ALL POSITION



SAFETY



LOW NOISE



WET BRAKING

A tread pattern suitable for use on all positions



Size and axle fitment	Load and speed index	EU tyre label			Winter marking	Other marking	Regrooving reference	Price/...../.....
		 ¹	 ²	 ³				
205/75 R 17.5 Steer	124/122M	D	C	 68 dB	 / M+S	TRACTION	1	
215/75 R 17.5 Steer	126/124M	D	C	 68 dB	 / M+S	TRACTION	1	
235/75 R 17.5 Steer	132/130M	D	C	 68 dB	 / M+S	TRACTION	1	
245/70 R 17.5 Steer	136/134M	D	B	 68 dB	 / M+S	TRACTION	1	
265/70 R 19.5 Steer	140/138M	C	C	 69 dB	 / M+S	TRACTION	1	

NEW MARKINGS: 3PMSE + TRACTION



TRAILER



SAFETY

Runs cooler



LONGEVITY



FUEL EFFICIENCY




Size and axle fitment	Load and speed index	Unique point	EU tyre label			Winter marking	Other marking	Regrooving reference	Price/...../.....
			 ¹	 ²	 ³				
215/75 R 17.5 Trailer	135/133J		D	B	 69 dB	M+S	FRT	2	
235/75 R 17.5 Trailer	143/141J	144F	C	B	 69 dB	M+S	FRT	2	
245/70 R 17.5 Trailer	143/141J	144F	C	B	 69 dB	M+S	FRT	2	
265/70 R 19.5 Trailer	143/141J		C	B	 69 dB	M+S	FRT	2	


● Recommended position ● Possible position

REGROOVING TABLES

Road Go Steer / All position

Blade	
R3	
Width	
6 to 8 mm	
Max Depth	
2 mm	

Road Go Trailer

Blade	
R3	
Width	
6 to 8 mm	
Max Depth	
2 mm	

All tyres are compliant with UNECE/R54 and ETRTO standards - (1) Fuel efficiency (from A to G) - (2) Wet grip (from A to G) - (3) External rolling noise class (from 1 to 3) & External rolling noise measured value (decibel) - (4) Respect the positions, fitting direction, direction of rotation and any relevant instructions when mentioned on the tyre sidewalls - (5) Measurement done between 2011 and 2016 during internal running test on 385/65R22.5 trailer tyres. Temperature 15°C lower in average for Orrium Tyre compare to 4 competitors representative of Tier 3 Tier 4 in the same dimension (DOUBLE COIN, LING LONG, MATADOR, TRIANGLE) - (6) Free Rolling Tyre

everyday use whatever the weather conditions.



ORIUM ROAD GO

HEAVY TRUCK
REGIONAL & LONG HAUL USE



STEER / ALL POSITION



SAFETY **LONGEVITY** **HANDLING**
Tread design with stone ejector and casing with Ultra High Tension Cable

Size and axle fitment	Load and speed index	Unique point	EU tyre label			Winter marking	Other marking	Regrooving reference	Price / /
			1	2	3				
295/80 R 22.5 Steer	152/148M		C	C	70 dB	M+S		3	
315/80 R 22.5 Steer	156/150L		C	B	70 dB	M+S		3	
315/70 R 22.5 Steer	154/150L		C	C	72 dB	M+S		3	
385/65 R 22.5 Steer	160K	158L	C	B	72 dB	M+S		3	



DRIVE



WINTER SAFETY **FUEL EFFICIENCY** **FITTING DIRECTION⁴**
3PMST and C Rolling resistance

Size and axle fitment	Load and speed index	EU tyre label			Winter marking	Other marking	Regrooving reference	Price / /
		1	2	3				
295/80 R 22.5 Drive	152/148M	C	C	73 dB	/ M+S	TRACTION	4	
315/80 R 22.5 Drive	156/150L	C	C	73 dB	/ M+S	TRACTION	4	
315/70 R 22.5 Drive	154/150L	C	C	73 dB	/ M+S	TRACTION	4	



TRAILER



SAFETY **LONGEVITY** **FUEL EFFICIENCY**
ORIUM runs 15°C cooler than competitors on 385/65 R 22.5 trailer tyres⁵

Size and axle fitment	Load and speed index	EU tyre label			Winter marking	Other marking	Regrooving reference	Price / /
		1	2	3				
385/65 R 22.5 Trailer	160K	C	C	70 dB	M+S	FRT ⁶	5	

Recommended position Possible position

REGROOVING TABLES Road Go Steer / All position

Blade		3
R3		
Width		
10 mm		
Max Depth		2 mm
2 mm		

Road Go Drive

Blade		4
R3		
Width		
10 mm		
Max Depth		2 mm
2 mm		

Road Go Trailer

Blade		5
R4		
Width		
10 mm		
Max Depth		2 mm
2 mm		



ORIUM URBAN GO

URBAN BUS



STEER / ALL POSITION



SAFETY

Reinforced sidewalls with wear indicator and quite ride



LONGEVITY



LOW NOISE

Size and axle fitment	Load and speed index	Unique point	EU tyre label			Winter marking	Other marking	Regrooving reference	Price / /
			 ¹	 ²	 ³				
275/70 R 22.5 Steer	150/148J		D	B	71 dB	M+S	TRACTION	6	

NEW MARKINGS: 3PMSF + TRACTION



ORIUM ON-OFF GO

HEAVY TRUCK
ON-OFF USE



STEER / ALL POSITION



ROBUSTNESS



LONGEVITY



HANDLING

A robust casing and tread pattern for your on-off road activity

Size and axle fitment	Load and speed index	EU tyre label			Winter marking	Other marking	Regrooving reference	Price / /
		 ¹	 ²	 ³				
315/80 R 22.5 Steer*	156/150K	C	B	71 dB	M+S		7	
13 R 22.5 Steer	156/150K	D	B	69 dB	M+S		7	
385/65 R 22.5 Steer**	160K	C	C	72 dB	M+S		7	



DRIVE



ROBUSTNESS



TRACTION IN MUD



LONGEVITY


A tread pattern designed for high traction and low stone retention

Size and axle fitment	Load and speed index	EU tyre label			Winter marking	Other marking	Regrooving reference	Price / /
		 ¹	 ²	 ³				
315/80 R 22.5 Drive	156/150K	D	B	75 dB	M+S	TRACTION	8	
13 R 22.5 Drive	156/150K	D	B	74 dB	M+S	TRACTION	8	



● Recommended position ● Possible position

REGROOVING TABLES Urban Go Steer / All position

Blade	
R3	
Width	
10 mm	
Max Depth	2 mm
2 mm	

On-Off Go Steer / All position

Blade	
R4	
Width	
10 mm	
Max Depth	2 mm
2 mm	

On-Off Go Drive

Blade	
R3	
Width	
10 mm	
Max Depth	2 mm
2 mm	

All tyres are compliant with UNECE/R54 and ETRTO standards - (1) Fuel efficiency (from A to G) - (2) Wet grip (from A to G) - (3) External rolling noise class (from 1 to 3) & External rolling noise measured value (decibel)