

GO THE DISTANCE

FS422 PLUS FD622 PLUS FT522 PLUS



Firestone

www.firestone.eu

You've got a full load behind you, unpredictable conditions ahead and a deadline to meet at the other end... Which is why you need versatile tyres you can trust to go the distance in the rough and ready world of regional transportation. Firestone's FS422 PLUS steer, FD622 PLUS drive and FT522 PLUS trailer tyres combine the performance, mileage, durability and value for money you need to keep on delivering, time and time again.

FS422 PLUS

GO THE EXTRA MILES










- The Equalizer Rib Design in combination with the multiple sipes provides high resistance to irregular wear as well as excellent wet and dry handling.
- 3 Extend the life of your tyres even further with robust, retreadable casings.
- 4 Enjoy a smooth, comfortable and quiet ride with noise-dampening Groove Fences and Variable Pitch Sipes.





FD622 PLUS

DRIVE YOUR BUSINESS FURTHER





- 1 Profit from a low total cost per kilometre thanks to the tyre's excellent mileage potential.
- **2** Get the grip you need for **excellent wet-weather handling** with a unique unidirectional pattern.
- 3 Extend the life of your tyres thanks to a sturdy construction and highly retreadable casings.

FT522 PLUS

CARRY THE LOAD





- 1 Profit from longer tyre life" thanks to a durable construction and good resistance to irregular wear.
- 2 Go even further with excellent retreading and regrooving capabilities.
- **3** Rely on solid, consistent handling, even in the wet.



PRODUCT TECHNOLOGIES



The Firestone PLUS truck tyres are built with a slim bead which significantly reduces the weight of the tyre for low fuel consumption and efficient performance.

EXTEND THE LIFE OF YOUR TYRES

Your tyres are a significant investment. Bandag, the retreading solution of Bridgestone/Firestone, helps you maximise your return and minimise your cost per km. Get the most out of your Firestone tyres. Welcome to Total Tyre Life!





AVAILABLE SIZES

Pattern	Size	Load/ Speed index	Section Width (mm)	Diameter (mm) Overall	Static Loaded Radius (mm)	Rolling Circ. (mm) @ 90 km/h (Tol, ± 2%)	Rim (Inch) Measuring	Rim (inch) Optional	_ 0	000	√3)))	dB	M + 5	
FS422 PLUS	295/80 R 22.5	152/148 M	298	1044	491	3205	8.25	9.00	С	В)))	71	<	<
	315/80 R 22.5	156/150 L	314	1068	497	3246	9.00	9.75	С	В	1)))	70		
1		154/150 M	514	1000	447	3240	7.00	7.75		٥	*/// 	70		•
315	315/70 R 22.5	154/150 L	314	1016	469	3089	9.00	9.75	С	В) ((c	71	•	•
		152/148 M												
	385/65 R 22.5	160 K/158 L				*								
FD622 PLUS	295/80 R 22.5	152/148 M	298	1055	486	3172	8.25	9.00	D	С)))	73	>	~
	315/80 R 22.5	156/150 L	314	1081	502	3286	9.00	9.75	D	С)))	72	•	•
		154/150 M												
	315/70 R 22.5	154/150 L	314	1027	474	3122	9.00	9.75	D	В))))	75		
		152/148 M	514	1027	4/4	3122	7.00	7.73				/3	~	•
FT522 PLUS	385/65 R 22.5	160 J	378	1078	498	3277	11.75	12.25	С	В)))	69	>	>